



SWCPS – Stormwater Construction Plan Submittal Checklist

Project Name _____ Date _____ New or Expansion (N/E)? _____

Project Acreage _____ Existing Impervious SF _____ Proposed Impervious SF _____ Disturbed Acreage _____

Applicant: Name _____ Address: _____ Phone: _____ Email: _____
 Engineer: Name: _____ Address: _____ Phone: _____ Email: _____

| Construction Plan Review Submittal Package Requirements | |
|---|---|
| Applicant shall select all applicable items below and provide with the submittal. | |
| General Requirements | |
| <input type="checkbox"/> | 1. Cover letter stating the purpose of the submission, describing site drainage, stormwater management objectives, and how the proposed stormwater management plan will meet the objectives and be implemented. |
| <input type="checkbox"/> | 2. Written Response to Comments |
| <input type="checkbox"/> | 3. All projects disturbing 1 acre or more shall be required to file a Notice of Intent (NOI) with Kansas department of Health and Environment (KDHE). Water quality structures or features shall be required per Manual for Construction Site - Best Management Practices (available on the City's Stormwater Management page). |
| <input type="checkbox"/> | 4. An engineering drainage study will be required for all projects to determine the impact of the proposed development on the existing drainage system and the need for detention. The report shall be submitted to the City with the preliminary plat or prior to any development in previously platted but yet undeveloped areas. The total tributary area (both project and downstream) in the drainage study shall account for a minimum of 10 times the tributary area released from the project site. Post-development flow shall not be greater than pre-development flow. |
| <input type="checkbox"/> | 5. Water quality treatment is required per the Manual For Post Construction - Best Management Practices (available on the City's Stormwater Management page) for sites with: |
| <input type="checkbox"/> | a. Impervious/Pervious ratios > 1.0 |
| <input type="checkbox"/> | b. Sites with hydrologic soil group B soils with Impervious/Pervious ratios > 0.95 |
| <input type="checkbox"/> | c. Sites with hydrologic soil group C soils with Impervious/Pervious ratios > 0.40 |
| <input type="checkbox"/> | d. Sites with hydrologic soil group D soils with Impervious/Pervious ratios > 0.06 |
| <input type="checkbox"/> | e. Sites draining to receiving waters with established TMDL or a sensitive waterbody |
| <input type="checkbox"/> | 6. Stream Corridor Overlay District Ordinance shall apply within the Minimum Stream Corridor Width as defined as: |
| <input type="checkbox"/> | a. 100 feet from edge of Sand Creek bank in both directions |



SWCPS – Stormwater Construction Plan Submittal Checklist

| | | | |
|------------------------------------|--------------------------|---|---|
| <input type="checkbox"/> | <input type="checkbox"/> | b. | 75 feet from edge of Slate Creek bank in both directions |
| <input type="checkbox"/> | <input type="checkbox"/> | c. | 75 feet from edge of Mud Creek bank in both directions |
| <input type="checkbox"/> | <input type="checkbox"/> | d. | 75 feet from edge of Jester Creek bank in both directions |
| <input type="checkbox"/> | 7. | Water Quantity Detention requirements shall apply to all development except: | |
| <input type="checkbox"/> | <input type="checkbox"/> | a. | Where downstream flooding is entirely confined within the limits of the 100-year floodplain as defined by the Federal Flood Insurance Study (FIS) current at the time the development is proposed. |
| <input type="checkbox"/> | <input type="checkbox"/> | b. | Additions to, improvement and repair of existing single-family and duplex dwellings. |
| <input type="checkbox"/> | <input type="checkbox"/> | c. | Remodeling, repair, replacement, and improvement to any existing structure or facility and appurtenances that does not cause an increased area of impervious surface on the site in excess of 10% of that which existed previously. |
| <input type="checkbox"/> | <input type="checkbox"/> | d. | Improvements on any site having a gross land area of one acre or less, regardless of land use. |
| <input type="checkbox"/> | <input type="checkbox"/> | e. | Construction of any one new single-family or duplex dwelling unit, irrespective of the total area of the site on which the structure is situated. |
| Drainage Study Requirements | | | |
| <input type="checkbox"/> | 1. | A contour interval of 1 foot or less is acceptable. All existing topography and the date of the topo survey shall be indicated. | |
| <input type="checkbox"/> | 2. | Bench Marks: At least one (1) bench mark adjacent to or within the proposed development shall be shown with the Mean Sea Level (MSL) Datum/National Geodetic Vertical Datum (NGVD). | |
| <input type="checkbox"/> | 3. | Plat Layout: The outline of all lots and blocks plus all permanent drainage easements shall be shown. The elevation of the 100-year water surface shall be indicated for all major system drainage easements. | |
| <input type="checkbox"/> | 4. | Provide drainage map showing drainage acres to the drainage features | |
| <input type="checkbox"/> | <input type="checkbox"/> | a. | Estimated pipe size (inches). |
| <input type="checkbox"/> | <input type="checkbox"/> | b. | Inlet locations. |
| <input type="checkbox"/> | <input type="checkbox"/> | c. | Basin and sub-basin boundaries. |
| <input type="checkbox"/> | 5. | Channels: Improved channels shall be indicated on the plan with the following data: | |
| <input type="checkbox"/> | <input type="checkbox"/> | a. | Approximate channel slope (percent). |
| <input type="checkbox"/> | <input type="checkbox"/> | b. | Estimated bottom width (feet). |
| <input type="checkbox"/> | <input type="checkbox"/> | c. | Proposed side slopes. |
| <input type="checkbox"/> | <input type="checkbox"/> | d. | Design discharge, Q (CFS). |
| <input type="checkbox"/> | 6. | Detention Areas: All detention facilities as shall be shown on the plan with the following data: | |
| <input type="checkbox"/> | <input type="checkbox"/> | a. | Static pool elevation, where applicable. |



SWCPS – Stormwater Construction Plan Submittal Checklist

| | | |
|---|-----|---|
| <input type="checkbox"/> | b. | Maximum water surface elevations for the 2, 10 and 100-year storms. |
| <input type="checkbox"/> | c. | Discharge rates for the 2, 10 and 100-year storms. |
| <input type="checkbox"/> | d. | Proposed size and type of control structure. |
| <input type="checkbox"/> | 7. | FEMA Data: The limits of the FEMA floodplain and floodway along with the Base Flood Elevations (BFE) shall be shown where appropriate. Where new development is proposed adjacent to unstudied or non-detailed studied streams, the developer shall submit the appropriate backwater calculations (based on HEC-2), encroachment analysis, and floodway data to be submitted to FEMA for review and approval. |
| <input type="checkbox"/> | 8. | Minimum Elevations: Minimum structure elevations shall be indicated for each lot adjacent to a dedicated drainage easement on the major drainage system. The minimum elevation shall be the elevation of the lowest point of entry or opening into any habitable structure on that lot. |
| <input type="checkbox"/> | 9. | Off-Site Drainage: All off-site drainage areas which discharge into the proposed development shall be labeled with the basin size (acres) and the 10 and 100-year peak discharges (CFS). |
| <input type="checkbox"/> | 10. | Street Grades: Preliminary street grades and elevations at sumps and crests shall be shown on the plan with arrows to indicate direction of drainage flows. |
| <input type="checkbox"/> | 11. | Stormwater Calculations: |
| <input type="checkbox"/> | a. | Support data for all stormwater practice designs, such as inflow/outflow rates, stage/storage data, hydrographs, outlet designs, infiltration rates, water elevations, design output, summary, etc. |
| <input type="checkbox"/> | b. | Other hydraulic and hydrologic computations critical to the plan/designs. |
| <input type="checkbox"/> | c. | Signature, Date And Professional Seal: for all Stormwater design management proposals, i.e. calculations, BMP designs, operations/maintenance/budget/asbuilt/inspections/manuals. |
| 12.0 Construction Plan Requirements | | |
| 12.1 Scope: This section governs the preparation of plans for stormwaters system construction projects. | | |
| 12.2 General: The plans shall include all information necessary to build and check the design of the storm drain systems. The plans shall be arranged as required by the City Engineer. Standard details of the city may be included by reference. Plans shall be sealed by the registered Professional Engineer and shall be submitted to the City Engineer for review and approval. | | |



SWCPS – Stormwater Construction Plan Submittal Checklist

12.3 Scale:

Plans shall be drawn at the following minimum scales. Larger scales may be needed to clearly present the design. Bar scales shall be shown on each sheet for each scale.

Plan: 1-inch=50 feet

Profile:

Vertical: 1-inch = 5 feet

Horizontal: 1-inch = 50 feet

Drainage Area Map:

On-site: 1-inch =200 feet

Off-site 1-inch = 1,000 feet

Structural Plans:1/4-inch = 1 foot

Graphic Drawings: Varies

12.4 Required Information:

| | | |
|--------------------------|---------------------------|---|
| A. | Drainage Area Map: | |
| <input type="checkbox"/> | 1. | Ridge line of the area tributary to each principal element of the system |
| <input type="checkbox"/> | 2. | The area in acres |
| <input type="checkbox"/> | 3. | The runoff coefficient “C” or curve number “CN” for each area, as applicable. |
| B. | Plan View | |
| <input type="checkbox"/> | 1. | Location/Vicinity Map |
| <input type="checkbox"/> | 2. | North arrow, graphic scale, drafting version date, legend and professional seal |
| <input type="checkbox"/> | 3. | Proposed improvements: roads, buildings, parking areas, grassed landscaped, and natural areas. |
| <input type="checkbox"/> | 4. | Delineation of current FEMA Flood boundaries |
| <input type="checkbox"/> | 5. | Ties to permanent reference point for each system located outside of the street right-of-way |
| <input type="checkbox"/> | 6. | Identification and location of each pipe. Culvert, inlet, structure, and existing utility affecting construction. |
| <input type="checkbox"/> | 7. | Right-of-way, property, and drainage easement lines. |
| <input type="checkbox"/> | 8. | Existing man-made and natural topographic features, such as buildings fences, trees, channels, ponds, streams, etc., and all existing and proposed utilities. |
| <input type="checkbox"/> | 9. | Locations of test borings |
| <input type="checkbox"/> | 10. | Existing and finish grade contours at intervals of 1.0 feet or less in elevation or equivalent detail indicating existing and finish grades and slopes |



SWCPS – Stormwater Construction Plan Submittal Checklist

| | | |
|--------------------------|-----|--|
| <input type="checkbox"/> | 11. | A uniform set of symbols subject to approval by the City Engineer. |
| <input type="checkbox"/> | 12. | The centerline of open channels within 50 feet of an enclosed drainage system and showing the direction of flow. |
| C. | | Profile View |
| <input type="checkbox"/> | 1. | Existing and finished surface grade along the centerline of pipe except street centerline may be used when construction includes street construction. |
| <input type="checkbox"/> | 2. | Length, size and slope of each line or channel segment. Slope shall be expressed in percent |
| <input type="checkbox"/> | 3. | Headwater elevation at the inlet end of each culvert |
| <input type="checkbox"/> | 4. | Flow line (invert elevation in and out) at each structure. |
| <input type="checkbox"/> | 5. | Each existing utility line crossing the alignment shall be properly located and identified as to type, size and material. |
| <input type="checkbox"/> | 6. | Test borings |
| <input type="checkbox"/> | 7. | All station and invert elevations of manholes, junction boxes, inlets, or other structures. |
| <input type="checkbox"/> | 8. | The profile shall show existing grade above the centerline as dashed line and proposed finish grades by solid lines. It shall also show the flow line of any drainage channel, either improved or unimproved, within 50 feet on either side of the centerline. Each line shall be properly identified. The proposed storm sewer shall be shown as double solid lines properly showing the top of the pipe. |
| <input type="checkbox"/> | 9. | All manholes, inlets, or other structures shall be shown and labeled with appropriate "Standard Drawing" designation. |
| D. | | Design Information |
| <input type="checkbox"/> | 1. | Tributary area in acres. |
| <input type="checkbox"/> | 2. | Design discharge and capacity in cubic feet per second. |
| <input type="checkbox"/> | 3. | Runoff coefficient "C" or curve number "CN", design storm return frequency (when Rational method is used for design) and Manning's "n" value. |
| <input type="checkbox"/> | 4. | Discharge velocity at design flow |
| <input type="checkbox"/> | 5. | Hydraulic grade line. |
| <input type="checkbox"/> | 6. | Type and grade of material (gage, class, etc.). |
| E. | | Long Term BMP Plan |
| <input type="checkbox"/> | 1. | Location and type of all proposed stormwater management structures (<i>grass swale, wet/dry detention basin, filtering/infiltration basin, bioretention, etc.</i>). |
| <input type="checkbox"/> | 2. | Legend with hatching indicating Existing Onsite Impervious Treated, Proposed Onsite Impervious Treated, Existing Offsite Impervious Treated, Existing Onsite Impervious Untreated, and Proposed Onsite Impervious Untreated. Indicate Square Feet of each hatching category. |
| <input type="checkbox"/> | 3. | Table with impervious calculations - existing and proposed impervious surfaces: roads, well lots, recreation sites, single family residences, etc. |



SWCPS – Stormwater Construction Plan Submittal Checklist

| | | |
|--------------------------|----|---|
| <input type="checkbox"/> | 4. | Details as required for proposed stormwater management structures |
| <input type="checkbox"/> | 5. | Operation, Inspection, & Maintenance Procedures |

Schedules which indicate all variable dimension and elevations covered by standards or “typical” drawings shall be shown on plans. All design details for nonstandard structures shall be indicated on the plans. A minimum of one plan view and one sectional view shall be shown on the plans for each structure. Additional views may be required. However, the grade, type, size and location of the bars shall be clearly indicated on the plans

Applicant Signature: _____

Date: _____